

Doodle Page Digital Download

This PDF file contains 1 (one) Doodle Page. The PDF has been put together to give you options when it comes to printing. Pages and patterns that are larger than 8½x11 have been provided in two formats:



1) Full Size

If you would like to have a full size print out, take the full size pages to your local print shop and they can print it for you. All full size Doodle Pages are 11x17



2) Tiled

The tiled pages give you the option of printing the full sized Doodle Pages at home. You print the tiled pages and then assemble them to make the larger patterns.


The Doodle Page PDF files are typically laid out like this:


Front – full sized, front – tiled, back – full sized, back – tiled (Some Doodle Pages do not have backs)

Please note: When printing on a home printer, the edges may get cut off. To avoid this, make sure "Page Scaling" is set to "Shrink to Printable Area" in the Adobe Reader print dialogue box. This will decrease the size of the Doodle Page a very small amount.



You may take this PDF file to your local print shop to have the full-size pages printed for your own personal use.





CRAFTOOLS and METALLIC LACQUERS (A Great Combination) by Dean Tinker

When working with Craftool stamped patterns the use of metallic lacquers as a color adds a dimension to the finished project which can't be duplicated in any other way.

Metallics are most comonly combined with other dyes and/or paints and are usually enhanced by the use of antiques,

A "rule" to consider when planning your color schemes; gold is used with "warm" colors (red, orange, brown) and silver is used with "cool" colors (blue, green, purple). Do not let this "rule" you but use as a guide only.

When left standing unused, metallic flake will settle to the bottom of container. Mix well before application. To control application, brush on.

Select your brush (camel hair). Apply to project directly from bottle or cap, dipping often because lacquer is rapid drying and may mar your working surface by "pilling up". Keep a container of lacquer thinner handy and clean brush occasionally to prevent buildup of dried lacquer on brush. Experiment to find your own best use.

Please observe the following general instructions in completing patterns on this page.

In working with these designs, remember that in quality handmade tools there is a slight size variance in tools in the same series number. Because of this, measurements in instructions may need adjustment.


Be sure to maintain alignment and spacings of tool impressions. In this you may wish to use a ruler until the eye becomes skilled through experience.


Try all patterns on scrap before finishing your belts.


Study photo of each pattern. Read instructions. It might be helpful to write construction highlights on a separate paper for easy reference to photo.

Be certain to case leather properly to insure deep impressions. If leather becomes too dry the stampings will be shallow and undefined.

All four belts here are to be constructed on 1½" width belt strips of carving quality leather.







CRAFTOOLS and METALLIC LACQUERS (A Great Combination) by Dean Tinker

When working with Craftool stamped patterns the use of metallic lacquers as a color adds a dimension to the finished project which can't be duplicated in any other way.

Metallics are most comonly combined with other dyes and/or paints and are usually enhanced by the use of antiques,

A "rule" to consider when planning your color schemes; gold is used with "warm" colors (red, orange, brown) and silver is used with "cool" colors (blue, green, purple). Do not let this "rule" you but use as a guide only.

When left standing unused, metallic flake will settle to the bottom of container. Mix well before application. To control application, brush on.

Select your brush (camel hair). Apply to project directly from bottle or cap, dipping often because lacquer is rapid drying and may mar your working surface by "pilling up". Keep a container of lacquer thinner handy and clean brush occasionally to prevent buildup of dried lacquer on brush. Experiment to find your own best use.

Please observe the following general instructions in completing patterns on this page.

In working with these designs, remember that in quality handmade tools there is a slight size variance in tools in the same series number. Because of this, measurements in instructions may need adjustment.

Be sure to maintain alignment and spacings of tool impressions. In this you may wish to use a ruler until the eye becomes skilled through experience.

Try all patterns on scrap before finishing your belts.

Study photo of each pattern. Read instructions. It might be helpful to write construction highlights on a separate paper for easy reference to photo.

Be certain to case leather properly to insure deep impressions. If leather becomes too dry the stampings will be shallow and undefined.

All four belts here are to be constructed on 1¼" width belt strips of carving quality leather.

BELT NO. 1

Craftools: C831, R875, V403, V404, V708.

STEP 1. Begin $\frac{1}{2}$ " in from tip. Measure 3/8" in from edges. Mark lightly. Center C831 vertically on marks. Repeat 3/8" from edges on opposite end.

STEP 2. On top marks scribe a very light line the length of strip. Repeat on lower marks.

STEP 3, Stamp V708 on both lines full length of strip.

STEP 4. Stamp C831 length of strip.

BELT NO. 2

Craftools: A100, C830, C834, V407.

STEP 1. Begin 3/8" in from tip. Measure ½" in from edges. Mark lightly. Center C830 vertically on marks. Repeat ½" from edges on opposite end.

STEP 2. Using top marks scribe a light guide line length of strip. Repeat on lower marks.

STEP 3. Stamp V407 to both lines full length of strip.

STEP 4. Stamp C830 length of strip.

BELT NO. 3

Craftools: A100, C828, C830, C831, V708, Swivel Knife.

STEP 1. Begin %'' in from tip. Find exact center. Mark lightly. Measure 3/8" from edges. Mark lightly. Repeat 3/8" in from opposite end. Mark lightly.

STEP 2. On top marks scribe a very light line length of strip. Repeat on middle and bottom lines.

STEP 3. With V708, on top scribed line stamp length of strip. Repeat on lower line.

STEP 4. Stamp C831 length of belt.

BELT NO. 4

Craftools: H904, J815, S705, V413, F976.

STEP 1. Begin $\frac{1}{4}$ " in from tip and find exact center. Mark. Center at opposite end. Mark. Do not scribe.

STEP 2. Align ruler on marks. From first mark ($\frac{1}{4}$ " in) measure 7/8". Mark. From this mark, measure $\frac{1}{4}$ ". Mark. Continue procedure length of strip.

STEP 3. From first mark, with V413, stamp center figure length of strip.

STEP 4. Complete stamping with V413 as shown.

STEP 5. Stamp C834 at top and bottom within circle.

STEP 6. A100 as indicated.

Bevel edges, Dye Dark Brown. Slick.

Colors: Tandy Super Tan, Zoe's Refinish Gold, Tandy Light Brown Antique.

Gold to first circle, Tan to second, Gold to third and continue full length. Do not allow color outside of scalloped edges. Antique overall. Quickly wipe excess. Slick edges. Carefully seal with "Super Shene".

STEP 5. Use center line as guide; stamp C830 full length.

STEP 6. A100 as indicated.

STEP 7. Apply decorative cuts with swivel knife as shown.

Bevel edges.

Colors: Tandy Super Black, Zoe's Refinish Gold and Silver, Tandy Black Antique.

Apply Zoe's Gold and Silver as shown. Apply antique overall. Wipe excess. Slick edges.

STEP 5. Stamp V403 full length. Stamp R875.

STEP 6. Lightly stamp V404 on each oval, staggering 4 horizontal and 3 vertical.

Bevel edges.

Colors: Tandy Super Tan, Cova Dye Turquoise, Zoe's Refinish Silver, Tandy Black Antique.

Color body of belt Tan. Turquiose Cova to ovals. Silver between ovals. Dye edges Black. Black antique overall. Wipe excess. Slick edges.


STEP 5. \$705 and H904 to center figures.


STEP 6. Complete pattern with J815.

Bevel edges.


Colors: Zoe's Refinish Gold and Silver, Tandy Super Dye Black, Tandy Black Antique.

Apply Zoe's as shown. Antique overall. Wipe excess. Slick edges. Tandy "Super Shene" to seal.





CREATIVE BELT STAMPING. Leathercrafter Paul Burnett shows you how to create 22 intricate designs using leather stamping tools. His step-by-step instructions include sizing belts and 5 dyeing and finishing techniques. 20 pages...........1909



BELT NO. 1

Craftools: C831, R875, V403, V404, V708.

STEP 1. Begin $\frac{1}{2}$ " in from tip. Measure 3/8" in from edges. Mark lightly. Center C831 vertically on marks. Repeat 3/8" from edges on opposite end.

STEP 2. On top marks scribe a very light line the length of strip. Repeat on lower marks

STEP 3. Stamp V708 on both lines full length of strip.

STEP 4. Stamp C831 length of strip.

STEP 6. A100 as indicated.

Bevel edges, Dye Dark Brown. Slick.

Colors: Tandy Super Tan, Zoe's Refin

STEP 5. Stamp C834 at top and botto

Gold to first circle, Tan to second, Go not allow color outside of scalloped excess. Slick edges. Carefully seal with

BELT NO. 2

Craftools: A100, C830, C834, V407.

STEP 1. Begin 3/8" in from tip. Measure $\frac{1}{2}$ " in from edges. Mark lightly. Center C830 vertically on marks. Repeat $\frac{1}{2}$ " from edges on opposite end.

STEP 2. Using top marks scribe a light guide line length of strip. Repeat on lower marks.

STEP 3. Stamp V407 to both lines full length of strip.

STEP 4. Stamp C830 length of strip.

STEP 5. Use center line as guide; stam

STEP 6. A100 as indicated.

STEP 7. Apply decorative cuts with s

Bevel edges.

Colors: Tandy Super Black, Zoe's Antique.

Apply Zoe's Gold and Silver as sho Slick edges.

BELT NO. 3

Craftools: A100, C828, C830, C831, V708, Swivel Knife.

STEP 1. Begin $\frac{1}{2}$ " in from tip. Find exact center. Mark lightly. Measure $\frac{3}{8}$ " from edges. Mark lightly. Repeat $\frac{3}{8}$ " in from opposite end. Mark lightly.

STEP 2. On top marks scribe a very light line length of strip. Repeat on middle and bottom lines.

STEP 3. With V708, on top scribed line stamp length of strip. Repeat on lower line.

STEP 4. Stamp C831 length of belt.

STEP 5. Stamp V403 full length. Star

STEP 6. Lightly stamp V404 on eavertical.

Bevel edges.

Colors: Tandy Super Tan, Cova Dye Black Antique.

Color body of belt Tan. Turquiose C edges Black. Black antique overall. Wi

BELT NO. 4

Craftools: H904, J815, \$705, V413, F976.

STEP 1. Begin ¼" in from tip and find exact center. Mark. Center at opposite end. Mark. Do not scribe.

STEP 2. Align ruler on marks. From first mark (¼" in) measure 7/8". Mark. From this mark, measure ½". Mark. Continue procedure length of strip.

STEP 3. From first mark, with V413, stamp center figure length of strip.

STEP 4. Complete stamping with V413 as shown.

STEP 5. S705 and H904 to center figure

STEP 6. Complete pattern with J815.

Bevel edges.

Colors: Zoe's Refinish Gold and Silve Antique,

Apply Zoe's as shown. Antique ove "Super Shene" to seal.

m within circle.

sh Gold, Tandy Light Brown Antique.

Id to third and continue full length. Do edges. Antique overall. Quickly wipe "Super Shene".

p C830 full length.

wivel knife as shown.

Refinish Gold and Silver, Tandy Black

wn. Apply antique overall. Wipe excess.

np R875.

ch oval, staggering 4 horizontal and 3


Turquoise, Zoe's Refinish Silver, Tandy


ova to ovals. Silver between ovals. Dye pe excess. Slick edges.

ıres.

r, Tandy Super Dye Black, Tandy Black

erall. Wipe excess. Slick edges. Tandy





CREATIVE BELT STAMPING. Leathercrafter Paul Burnett shows you how to create 22 intricate designs using leather stamping tools. His step-by-step instructions include sizing belts and 5 dyeing and finishing techniques. 20 pages............1909

